

## TECHNICAL DATA

# Fluke 377, 378 Non-Contact Voltage True-rms AC/DC Clamp Meters with iFlex



### MEASURE VOLTAGE AND CURRENT

With your clamp jaw

### FASTER, SAFER TESTING

All without touching a live wire - using FieldSense™ technology

### POWER QUALITY INDICATOR

Shows whether equipment or power line is faulty

### COMPLETE 3-PHASE VOLTAGE AND CURRENT TESTS

in 3 quick steps

### Voltage and current measurements with FieldSense™ technology

The Fluke 377 and 378 true-rms clamp meters use Field-Sense™ technology to make testing faster and safer, all without touching a live conductor. You get accurate voltage and current measurements through the clamp jaw. Simply clip the black test lead to any electrical ground, put the clamp jaw around the conductor and see reliable, accurate voltage and current values on the display.

### Power quality indicator shows whether a problem is in the equipment or the power line

The 378 clamp meter includes a unique PQ function that senses power quality issues automatically. When making FieldSense measurements, the 378 will detect and display power quality issues, relating to current, voltage, power factor or any combination of the three. Now you can quickly determine if an upstream supply problem exists, or if there is a downstream equipment problem.




The 378 includes a power quality test that provides quick indication of whether an incoming power problem or an equipment problem exists.

# Specifications

## General specifications

|  |   |
|--|---|
| General Maximum voltage<br>(between any terminal and earth ground) | 1000 V  |
| <b>Battery</b>   |   |
| Type   | 2 AA IEC LR6 alkaline   |
| Life   | 200 hours   |
| Display  | Dual readout  |
| Automatic Power Off  | 20 minutes  |
| <b>AC Current: Jaw</b>   |   |
| Range  | 999.9 A   |
| Resolution   | 0.1 A   |
| Accuracy   | 2 % ± 5 digits (10 Hz to 100 Hz)<br>2.5 % ± 5 digits (100 Hz to 500 Hz) |
| Crest Factor (50/60 Hz)  | 3 @ 500 A<br>2.5 @ 600 A<br>1.42 @ 1000 A<br>Add 2 % for C.F. >2        |
| <b>AC Current: Flexible Current Probe</b>                          |   |
| Range  | 2500 A  |
| Resolution   | 1 A (≤ 2500 A) 0.1 A (≤ 999.9 A)  |
| Accuracy   | 3 % ± 5 digits (5 Hz to 500 Hz)   |



| Distance from Optimum | i2500-10 Flex    | i2500-18 Flex    | Error   |
|-----------------------|------------------|------------------|---------|
| A                     | 0.5 in (12.7 mm) | 1.4 in (35.6 mm) | ± 0.5 % |
| B                     | 0.8 in (20.3 mm) | 2.0 in (50.8 mm) | ± 1.0 % |
| C                     | 1.4 in (35.6 mm) | 2.5 in (63.5 mm) | ± 2.0 % |

Measurement uncertainty assumes centralized primary conductor at optimum position, no external electrical or magnetic field, and within operating temperature range.

|                               |                                 |
|-------------------------------|---------------------------------|
| <b>DC Current</b>             |                                 |
| Range                         | 999.9 A                         |
| Resolution                    | 0.1 A                           |
| Accuracy                      | 2 % ± 5 digits                  |
| <b>AC Voltage: FieldSense</b> |                                 |
| Range                         | 1000 V                          |
| Resolution                    | 1 V (≤ 1000 V)                  |
| Accuracy                      |                                 |
| ≤ 4/0 AWG                     | 3 % ± 5 digits (45 Hz to 66 Hz) |
| ≥ 4/0 AWG                     | 5 % ± 5 digits (45 Hz to 66 Hz) |



Position wire as close as possible to jaw opening (see illustration).

## Specifications (continued)

|   |  |
|---|--|
| <b>AC Voltage: Test Leads</b>                                       |  |
| Range   | 600.0 V 1000 V   |
| Resolution  | 0.1 V ( $\leq 600.0$ V)<br>1 V ( $\leq 1000$ V)  |
| Accuracy  | 1 % $\pm 5$ digits (20 Hz to 500 Hz)   |
| <b>DC Voltage</b>   |  |
| Range   | 600.0 V<br>1000 V  |
| Resolution  | 0.1 V ( $\leq 600.0$ V)<br>1 V ( $\leq 1000$ V)  |
| Accuracy  | 1 % $\pm 5$ digits   |
| <b>mV dc</b>  |  |
| Range   | 500.0 mV   |
| Resolution  | 0.1 mV   |
| Accuracy  | 1 % $\pm 5$ digits   |
| <b>Amps Frequency: Jaw</b>  |  |
| Range   | 5.0 Hz to 500.0 Hz   |
| Resolution  | 0.1 Hz   |
| Accuracy  | 0.5 % $\pm 5$ digits   |
| Trigger Level   | 5 Hz to 10 Hz, $\geq 10$ A<br>10 Hz to 100 Hz, $\geq 5$ A<br>100 Hz to 500 Hz, $\geq 10$ A                               |
| <b>Amps Frequency: Flexible Current Probe</b>                       |  |
| Range   | 5.0 Hz to 500.0 Hz   |
| Resolution  | 0.1 Hz   |
| Accuracy  | 0.5 % $\pm 5$ digits   |
| Trigger Level   | 5 Hz to 20 Hz, $\geq 25$ A<br>20 Hz to 100 Hz, $\geq 20$ A<br>100 Hz to 500 Hz, $\geq 25$ A                              |
| <b>Resistance</b>   |  |
| Range   | 60.00 k $\Omega$<br>6000 $\Omega$<br>600.0 $\Omega$  |
| Resolution  | 0.1 $\Omega$ ( $\leq 600.0$ $\Omega$ )<br>1 $\Omega$ ( $\leq 6000$ $\Omega$ )<br>10 $\Omega$ ( $\leq 60.00$ k $\Omega$ ) |
| Accuracy  | 1 % $\pm 5$ digits   |
| <b>Capacitance</b>  |  |
| Range   | 1000 $\mu$ F   |
| Resolution  | 0.1 $\mu$ F ( $\leq 100.0$ $\mu$ F)<br>1 F ( $\leq 1000$ $\mu$ F)  |
| Accuracy  | 1 % $\pm 4$ digits   |
| <b>Mechanical</b>   |  |
| Size (L x W x H)  | 274 mm x 86 mm x 47 mm   |
| Weight (with Batteries)   | 463 g  |
| Jaw Opening   | 34 mm  |
| Flexible Current Probe Diameter                                     | 7.5 mm   |
| Flexible Current Probe Cable Length (head to electronics connector) | 1.8 m  |
| Rogowski Coil Length  | 450 mm   |

|  |  |
|--|--|
| <b>Environmental</b>                           |  |
| Operating Temperature                          | -10 °C to 50 °C  |
| Storage Temperature                            | -40 °C to 60 °C  |
| Operating Humidity (without condensation)      | Non condensing (<10 °C)<br>≤ 90 % RH (10 °C to 30 °C)<br>≤ 75 % RH (30 °C to 40 °C)<br>≤ 45 % RH (40 °C to 50 °C)  |
| Temperature Coefficients                       | Add 0.1 x specified accuracy for each degree C >28 °C or <18 °C  |
| Ingress Protection                             | IEC 60529: IP30 (jaw closed)   |
| Operating Altitude                             | 2000 m   |
| Storage Altitude                               | 12 000 m   |
| <b>Electromagnetic Compatibility (EMC)</b>     |  |
| International                                  | IEC 61326-1: Portable Electromagnetic Environment<br>IEC 61326-2-2, CISPR 11: Group 1, Class B<br><br>Group 1: Equipment has intentionally generated and/or uses conductively-coupled radio frequency energy that is necessary for the internal function of the equipment itself.<br><br>Class B: Equipment is suitable for use in domestic establishments and in establishments directly connected to a low voltage power supply network which supplies buildings used for domestic purposes. Emissions that exceed the levels required by CISPR 11 can occur when the equipment is connected to a test object. |
| Korea (KCC)                                    | Class A equipment (Industrial Broadcast & Communications Equipment)<br><br>Class A: Equipment meets requirements for industrial electromagnetic wave equipment and the seller or user should take notice of it. This equipment is intended for use in business environments and not to be used in homes.   |
| USA (FCC)                                      | 47 CFR 15 subpart B. This product is considered an exempt device per clause 15.103.  |
| <b>Safety</b>                                  |  |
| General  | IEC 61010-1: Pollution degree 2  |
| Measurement                                    | IEC 61010-2-032: CAT III 1000 V / CAT IV 600 V<br>IEC 61010-2-033: CAT III 1000 V / CAT IV 600 V   |
| Current Clamp for Leakage Current Measurements | IEC 61557-13: Class 2, ≤ 30 A/m  |
| <b>Wireless Radio</b>                          |  |
| Radio Frequency Certification                  | FCC ID: T68-FBLE IC:6627A-FBLE   |
| Frequency Range                                | 2405 MHz to 2480 MHz   |
| Output Power                                   | <100 mW  |
| Radio Frequency Data                           | Go to <a href="http://www.fluke.com">www.fluke.com</a> and search for "Radio Frequency Data for Class A" (PN 4333628) SIMPLIFIED EU DECLARATION OF CONFORMITY Hereby, Fluke declares that the radio equipment contained in this Product is in compliance with Directive 2014/53/EU. The full text of the EU declaration is available at the following internet address: <a href="http://www.fluke.com/declaration-of-conformity">www.fluke.com/declaration-of-conformity</a>   |

## Ordering information

### FLUKE-378

#### Included

Fluke 378 Non-Contact Voltage True-rms AC/DC Clamp Meter

**TL224** Test Leads

**TP175** TwistGuard™ Test Probes

**AC285** black grounding clip (1 only)

**i2500-18 iFlex®** Flexible Current Probe 18 inch (48 cm)

**TPAK** ToolPak™ Magnetic Meter Hanger

Premium carrying case

Quick reference guide

### FLUKE-377

#### Included

Fluke 377 Non-Contact Voltage True-rms Wireless AC/DC Clamp Meter

**TL224** Test Leads

**TP175** TwistGuard™ Test Probes

**AC285** black grounding clip (1 only)

**i2500-18 iFlex®** Flexible Current Probe 18 inch (48 cm)

**TPAK** ToolPak™ Magnetic Meter Hanger

Premium carrying case

Quick reference guide

Visit [www.fluke.com](http://www.fluke.com) to get complete details on these products or ask your local Fluke sales representative.

## Voltage and current measurements with FieldSense™ technology

No more hand-written notes or complicated math.

- Complete 3-phase voltage and current tests in 3 easy steps
- Full set of phase-to-ground and phase-to-phase values calculated

## Measure extremely high current with iFlex™ probe

Use the included iFlex flexible current probe to measure ac current as high as 2500 A. The iFlex probe provides access to large conductors in tight spaces.

## Easy to see, easy to use with included tools

Your job will get easier when you use the 377 and 378 clamp meter:

- The display turns green when a stable FieldSense measurement is detected.
- Visual Continuity provides a bright green screen for easy detection of continuity in noisy work areas.
- The TPAK magnetic hanging kit, with 9 inch (23 cm) hanging strap, lets you hang your clamp wherever you need: to a steel cabinet door; around a pipe; on a nail or screw head.
- The included carrying case holds the clamp, iFlex probe, test leads and the included black grounding clip.

**Fluke.** *Keeping your world up and running.®*

#### Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

#### Fluke Europe B.V.

PO Box 1186, 5602 BD Eindhoven, The Netherlands

Modification of this document is not permitted without written permission from Fluke Corporation.

#### For more information call:

In the U.S.A. (800) 443-5853 or  
Fax (425) 446-5116  
In Europe/M-East/Africa +31 (0)40 267 5100 or  
Fax +31 (0)40 267 5222  
In Canada (800)-36-FLUKE or  
Fax (905) 890-6866  
From other countries +1 (425) 446-5500 or  
Fax +1 (425) 446-5116  
Web access: <http://www.fluke.com>

©2020 Fluke Corporation.  
Specifications subject to change without notice.  
3/2020 6013559a-en